

Veedol ATF III-G

Material no. 03204P253

DESCRIPTION

Veedol ATF III-G is a high grade automatic transmission fluid formulated with solvent refined base oils and a number of select additives to give the following benefits:

- Specific friction properties for smooth switching and driving comfort
- Very high and stable viscosity index
- Very good stability against oxidation
- Positive activity against wear, corrosion and foaming
- Perfect compatibility with seals and non-ferro metals

APPLICATION

This red coloured fluid is used for automatic gear boxes, power steering units, torque converters and other equipment for which an ATF Dexron II-E, III-F, III-G, III-H and/or Ford Mercon fluid is required.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Allison C4
 Daimler Truck DTFR 13C140/DTFR 13C150/DTFR 13C170
 Ford Mercon
 GM 6417-M Dexron III-G/Dexron II-D/Dexron III-H
 MAN 339 V1/Z1
 MB 236.5/236.6/236.7/236.8/236.9
 Voith H55.6335xx
 Volvo STD 1273,25 (97325)/STD 1273,35 (97335)/STD 1273,37 (97337)/STD 1273,40 (97340)/
 STD 1273,41 (97341)
 ZF TE-ML 03D/04D/05L/09/11B/14A/17C/21L

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.847
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	33,9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7,1
Viscosity index, ASTM D2270	179
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	17500
Flash Point COC, ASTM D92, °C	196
Colour, VISUAL	RED