

# Veedol ATF DSG

Material no. 03204P255

## DESCRIPTION

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes. This fluid gives the following benefits:

- Anti-wear protection: significantly extended transmission life
- Frictional properties: very smooth gear shifting, no vibration.
- Extended oil life: excellent thermal and oxidation stability.

## APPLICATION

Mainly intended for the DSG (Direct Shift Gearbox) of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc. This product is not intended for VW dry clutch DSG type 0AM, 02M, 02Q and 02S.

## PERFORMANCE SPECIFICATIONS

API GL-4

### Veedol recommends for

BMW 83220306816/83220397244/83220440214/83222147477/83222148578/83222148579/  
83222167666/83222409710/83222433157/DCTF-2/DTF 1/FFL-4/MTF LT-3/DCTF-1/MTF LT-5  
Chrysler 68044345EA  
Daimler Truck DTFR 13C130  
Ferrari TF DCT-F3  
Fiat 9.55550-DA11/-MZ2/-MZ6  
Ford F-DC/WSS-M2C200-D2/WSS-M2C200-D3/WSS-M2C200-E1/WSS-M2C218-A1/WSS-  
M2C936-A  
GM FFL-4  
Honda MTF III  
MB 236.21/236.24/236.25/239.21/SLS A0019898603  
McLaren FFL-4  
Mitsubishi Diamond Queen SSTF-1  
Nissan 999MP-6TRT00P/DCT Fluid/GR6/GT-R R35/LV MTF-1/R35 Special  
Porsche 000.043.20/000.043.207.29/000.043.207.30/000.043.305.63/999.917.080.00/  
999.917.080.01/999.917.546.00/TF 0870  
PSA 1618078480/9730 A8/9734 S2/JWS 2271  
Renault 7711785243/ BOT450 EDC 6-Speed/DC4/DW5  
Suzuki 99000-22B27-036  
Toyota JWS 227/1161839/BOT341 #1161838  
VW G 009 317/G 052 171/G 052 178/G 052 182/G 052 512/G 052 513/G 052 527/G 052 529/  
G 052 726/G 052 798/G 055 512/G 055 529/G 055 549/G 060 726/G 070 726/TL 521 82

# Veedol ATF DSG

Material-Nr. 03204P255

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.848
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	33.6
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	6.87
Viscosity index, ASTM D2270	170
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	11000
Flash Point COC, ASTM D92, °C	198