

Veedol ATF 8-G

Material no. 03204T259

DESCRIPTION

Veedol ATF 8-G is a high grade full synthetic automatic transmission fluid formulated with a number of special base oils and additives. This fluid gives the following benefits:

- Very good oxidation stability and very high thermal stability
- Excellent and very stable friction characteristics for longer oil change intervals
- Outstanding fuel saving potential
- Excellent lubrication
- Extensive protection against foaming
- Very good protection against wear
- Very high and stable viscosity index

APPLICATION

ATF 8-G was formulated especially for ZF 8HP transmissions. Thanks to its very low viscosity, this product makes a major contribution to reducing fuel consumption. ATF 8-G can be used for the 8 speed ZF automatic transmissions series as well as certain 6 and 9 speed ones.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

BMW 83 22 2 289 720/83222152426/ATF3+
 Chrysler 68157995AA
 Fiat 9.55550-AV5
 Jaguar 02JDE26444
 Land Rover LR023288
 MB 236.82
 VW G 060 162

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.851
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	31.9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	6.32
Viscosity index, ASTM D2270	153
Pour point, ASTM D6892, °C	-48
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	<=20000
Flash Point COC, ASTM D92, °C	210
Colour, VISUAL	GREEN