

Veedol Coolant XC

Material no. 03208P519

DESCRIPTION

Veedol Coolant XC is a "long life" OAT (Organic Additives Technology) automotive coolant based on monoethyleneglycol and demineralized water with special additives to obtain the following properties:

- Perfect protection of all types of metals that are used in engines and cooling systems
- Neutral behaviour towards seals, gaskets and hoses
- Very good resistance to formation of foam
- Nitrite, amine, phosphate and silicate free

APPLICATION

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -36°C.

PERFORMANCE SPECIFICATIONS

| | |
|------------------------------|------------------------------|
| Veedol recommends for | JIS K2234 |
| AFNOR NF R 15-601 | Liebherr Minimum LH-01-COL3A |
| ASTM D3306/D4656/D4985/D6210 | MAN 324 Si-OAT |
| BS 6580 | MB 326.5/326.6 |
| Cummins CES 14603 | MTU MTL 5048 |
| Cuna NC 956-16 | SAE J1034 |
| Daimler Truck DTFR 29D120 | UNE 26-361-88/1 |
| Deutz DQC CC-14 | VW TL 774-G |
| FFV Heft R443 | |

TYPICAL CHARACTERISTICS

| | |
|---|-------------|
| pH, ASTM, D1287 | 8.2 |
| Density at 20°C, ASTM D4052, g/ml | 1.069 |
| Colour | VISUAL PINK |
| Freezing point (refracto), ASTM D3321, °C | -36 |
| Water content, ASTM D1123, % wt/wt | 50 |