

Veedol Racing Plus 2T

Material no. 03206P351

DESCRIPTION

Veedol Racing Plus 2T is a two stroke engine oil formulated with carefully selected high quality mineral and synthetic base oils and special two stroke additives to give the following benefits:

- Perfect lubrication of all motor parts
- Active detergency, preventing deposits in the combustion zone and in the scavenger ports
- Prevents spark plugs from fouling, thereby securing an optimal output of the engine
- Very effective protection against wear and corrosion
- Very limited formation of smoke
- Self-mixing

APPLICATION

This two stroke engine oil is recommended for the lubrication of high speed aircooled two stroke engines under heavy duty loads. It may also be used for water cooled two stroke engines (with radiator type cooling systems). Dosage between 2% and 4% according to the manufacturer's recommendations.

PERFORMANCE SPECIFICATIONS

API TC
ISO L-EGD
Jaso FC / FD

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.870
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	76.8
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	10.4
Viscosity index, ASTM D2270	120
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	1.7
Flash Point COC, ASTM D92, °C	106
Colour, VISUAL	BLACKISH GREEN