

Veedol Transmission Synthetic 75W-90

Material no. 03203T216

DESCRIPTION

Veedol Transmission Synthetic 75W-90 is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials. This transmission oil gives the following benefits:

- Excellent frictional properties: very smooth gear shifting, no vibration
- Anti-wear and oxidation stability: superior protection of critical parts
- Extended oil life: excellent thermal and oxidation stability

APPLICATION

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.). of trucks and four-wheel drive vehicles.

PERFORMANCE SPECIFICATIONS

API GL-4/GL-5/MT-1	Veedol recommends for	MB 235.8/235.11
SAE J 2360	Arvin Meritor 0-76-N	MIL PRF-2105E
	BMW OSP	Renault B0032/3 Annex 3
	Chrysler MS 9763	SAE J 2360
	Daimler Truck DTFR 12B140	Scania STO 1
	Daimler Truck DTFR 13B110	Volvo 97312
	DAF GL5/MIL-PRF-2105E	ZF TE-ML 02B/05B/07A/08/
	Iveco MIL-PRF-2105E	12B/12L/12N/16F/17B/
	MACK GO-J	19C/21B
	MAN 341 Z-2/342 M-3/341 E-3	

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.862
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	70.2
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	15.0
Viscosity index, ASTM D2270	226
Pour point, ASTM D6892, °C	-42
CCS viscosity at -40°C, ASTM D5293, mPa.s	80.000