



Veedol Powertron F 5W20

Material no. 03201P008

DESCRIPTION

Veedol Powertron F 5W-20 is a fuel economy synthetic engine oil specially developed to meet the requirements of the latest Ford Ecoboost gasoline engines. It is developed using the most recent additive technology in combination with specially selected synthetic base oils with a high natural viscosity index. This has resulted in a well-balanced engine oil to give the following benefits:

- Lower fuel consumption
- High and very stable viscosity index
- High resistance to shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Reduced formation of combustion ashes

APPLICATION

Veedol Powertron F 5W-20 is based on synthetic base oils specially developed for the Ford Ecoboost gasoline engines. This engine oil can also be used as a ACEA A1/B1 or API SN product if recommended by the car manufacturer.

PERFORMANCE SPECIFICATIONS

ACEA C5/A1/B1
API SN
ILSAC GF-5
Ford WSS-M2C948-B/-A

Veedol recommends for
Jaguar Land Rover: STJLR.03.5004

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.851
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	42.3
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7.9
Viscosity index, ASTM D2270	162
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	7.6
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5500
Sulfated Ash, ASTM D874, Mass %	0.8
Flash Point COC, ASTM D92, °C	220