

Veedol Powertron Plus 5W40

Material no. 03201P012

DESCRIPTION

- Veedol Powertron Plus 5W-40 is a modern, synthetic, universal motor oil based on specially selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to give the following benefits:
- • High and very stable viscosity index
- • High resistance to shearing
- • Fast cold start
- • Very strong resistance to oxidation
- • Safe lubrication film at very high temperatures
- • Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Powertron Plus 5W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which modern specifications are required.

PERFORMANCE SPECIFICATIONS

ACEA A3/B4
API SN/CF

Approval
VW 502 00/505 00

Veedol recommends for

BMW Longlife-01
Fiat 9.55535-H2/-M2/-Z2
MB 226.5/229.3
Opel GM-LL-A-025/GM-LL-B-025
Porsche A40
PSA B71 2296
Renault RN 0700/RN 0710

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.858
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	86.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	14.4
Viscosity index, ASTM D2270	175
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.5
Pour point, ASTM D6892, °C	-45
CCS viscosity at -30°C, ASTM D5293, mPa.s	6100
Sulfated Ash, ASTM D874, Mass %	1.27
Flash Point COC, ASTM D92, °C	220