

Veedol Sintron C2/C3 5W30

Material no. 03201T006

DESCRIPTION

Veedol Sintron C2/C3 5W-30 is a universal, synthetic fuel economy motor oil developed according to the most recent technology. It is formulated using specially selected synthetic base oils with high viscosity index and a well-balanced choice of advanced additives. This oil gives the following benefits:

- Improved fuel efficiency
- High and shear stable viscosity index
- Excellent low temperature fluidity ensuring easy cold start
- Effective lubrication at very high temperatures
- Unique detergent/dispersion additive system ensuring high engine cleanliness with negligible sludge
- Reduced formation of combustion ashes
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Sintron C2/C3 5W-30 is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEMs and thus has a wide application.

PERFORMANCE SPECIFICATIONS

ACEA C2/ACEA C3
API SN

Approvals

BMW Longlife-04
MB-Approval 229.51
MB-Approval 229.52
VW 505 00/505 01

Veedol recommends for

Fiat 9.55535-S1/S3
GM dexos2™
MB 229.31
Renault RN17

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	70.9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	12.0
Viscosity index, ASTM D2270	167
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C	-45
Sulfated Ash, ASTM D874, Mass %	0.78

Version 11/08/2023