

Veedol Sintron F 5W30

Material no. 03201T007

DESCRIPTION

Veedol Sintron F 5W-30 is a modern synthetic fuel economy motor oil produced with select synthetic base oils and advanced additives to give the following benefits:

- Lower fuel consumption
- High and stable viscosity index
- High resistance to shearing
- Fast cold start
- Very strong resistance to oxidation
- Safe lubrication film at high temperatures
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Sintron F 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. It is specially developed for the requirements of Ford WSS-M2C913-C/D specifications. This oil is fully backwards compatible with Ford M2C913-A/B.

PERFORMANCE SPECIFICATIONS

ACEA A1/B1, A5/B5
API SL/CF
Ford WSS-M2C913-C/D

Veedol recommends for
Jaguar Land Rover: STJLR.03.5003
Renault RN 0700

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	55.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.95
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	4200
Sulfated Ash, ASTM D874, Mass %	1.09
Flash Point COC, ASTM D92, °C	210