

Veedol Sintron Ultra 0W20

Material no. 03201T026

DESCRIPTION

Veedol Sintron Ultra 0W-20 is a fuel economy motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to give the following benefits:

- Lower fuel consumption
- High and stable viscosity index
- Good resistance to shearing
- Fast cold start, even at very low temperatures
- Safe lubrication film at very high temperatures
- Very strong protection against wear, corrosion and foaming

APPLICATION

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. By its unique composition, this oil is also excellent for Hybrid and other Eco versions as brought by various OEMs. Due to its special composition, this product functions well in very low temperatures, and even under arctic conditions.

PERFORMANCE SPECIFICATIONS

API SN Plus	Veedol recommends for
API SP/RC	Acura
API SN/RC	Buick
API SP	Cadillac
ILSAC GF-6 A/GF-5	Chevrolet
Ford WSS-M2C945-A	Chrysler MS 6395
Ford WSS-M2C946-A	Dodge
Ford WSS-M2C947-A	Fiat 9.55535-CR1/-GSX
Ford WSS-M2C962-A	GM Dexos1 TM Gen 2/3
	GMC
	Jeep

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052 g/ml	0.847
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	44.6
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	8.52
Viscosity index, ASTM D2270	172
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7.4
Pour point, ASTM D6892, °C	-39
Sulfated Ash, ASTM D874, Mass %	0.79
Flash Point COC, ASTM D92, °C	220

Version 12/12/2023