

# Veedol Multigrade Super 10W40

Material no. 03201M014

## DESCRIPTION

Veedol Multigrade Super 10W-40 motor oil is based on a combination of highquality solvent refined mineral and synthetic base oils. By adding a wellbalanced choice of additives the following properties are obtained:

- High and stable viscosity index
- Fast cold start
- Strong resistance against oxidation
- Good detergency and dispersion
- Safe lubrication film at high temperatures
- Strong protection against wear, corrosion and foaming

## APPLICATION

**Veedol Multigrade Super 10W-40** is recommended for use in petrol and dieselengines, with or without turbo-charging, in passenger cars and delivery vans.

## PERFORMANCE SPECIFICATIONS

ACEA A3/B3  
ACEA A3/B4  
API SL/CF

### Veedol recommends for

MB 229.1  
VW 501 01  
VW 505 00

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.866
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	91
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	13.8
Viscosity index, ASTM D2270	155
B.N. (HClO <sub>4</sub> method), ASTM D2896, mg KOH/g	8.3
Pour point, ASTM D6892, °C	-39
CCS viscosity at -25°C, ASTM D5293, mPa.s	6700
Sulfated Ash, ASTM D874, Mass %	1.0
Flash Point COC ASTM D92, °C	220