

Veedol Multigrade Plus 15W40

Material no. 03201M015

DESCRIPTION

Veedol Multigrade Plus 15W-40 is a modern multifunctional motor oil, produced with high quality solvent refined base oils and modern additives to give the following benefits:

- Good wear protection
- Strong detergency and dispersion power
- Good resistance to oxidation
- Strong protection against corrosion and foaming
- High and stable viscosity index
- Low evaporation rate

APPLICATION

Veedol Multigrade Plus 15W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

PERFORMANCE SPECIFICATIONS

ACEA A3/B3, A3/B4
API SL/CF

Veedol recommends for

MB 229.1
VW 501 01/505 00

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.885
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	103
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13.7
Viscosity index, ASTM D2270	130
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	8.3
Pour point, ASTM D6892, °C	-39
CCS viscosity at -20°C, ASTM D5293, mPa.s	6800
Sulfated Ash, ASTM D874, Mass %	1.03
Flash Point COC, ASTM D92, °C	230