

Veedol Turbostar 20W50

Material no. 03201M017

DESCRIPTION

- Excellent protection against oxidation
- Excellent anti-wear properties
- Extensive protection against corrosion and foam formation
- Very strong dispersing and detergent effect
- Very high and stable viscosity index
- Low evaporation rate

APPLICATION

This versatile engine oil is ideal for gasoline and diesel engines as well as liquefied gas engines, with or without turbocharger, in cars or vans.

PERFORMANCE SPECIFICATIONS

ACEA A3/B3
ACEA A3/B4
API SL/CF

Veedol recommends for

MB 229.1
VW 501 01
VW 505 00

TYPICAL CHARACTERISTICS

| | |
|---|-------|
| Density at 15°C, ASTM D4052, g/ml | 0.890 |
| Kinematic viscosity at 40°C, ASTM D445, mm ² /s | 155 |
| Kinematic viscosity at 100°C, ASTM D445, mm ² /s | 18.0 |
| Viscosity index, ASTM D2270 | 125 |
| B.N. (HClO ₄ method), ASTM D2896, mg KOH/g | 8.3 |
| Pour point, ASTM D6892, °C | -24 |
| CCS viscosity at -15°C, ASTM D5293, mPa.s | 8800 |
| Sulfated Ash, ASTM D874, Mass % | 1,03 |
| Flash Point COC, ASTM D92, °C | 235 |