

Veedol Powertron F 5W20

Material no. 03201P008

DESCRIPTION

Veedol Powertron F 5W-20 is a fuel economy synthetic engine oil specially developed to meet the requirements of the latest Ford Ecoboost gasoline engines. It is developed using the most recent additive technology in combination with specially selected synthetic base oils with a high natural viscosity index. This resulted in a well-balanced engine oil where the following properties are obtained:

- Lower fuel consumption
- High and very stable viscosity index
- High resistance against shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Reduced formation of combustion ashes
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Powertron F 5W-20 is based on synthetic base oils specially developed for the Ford Ecoboost gasoline engines. This engine oil can also be used where an ACEA A1/B1 or API SN product is recommended by the car manufacturer.

PERFORMANCE SPECIFICATIONS

ACEA C5
ACEA A1/B1
API SN
Ford WSS-M2C948-B
Ford WSS-M2C948-A
ILSAC: GF-5

Veedol recommends for

Jaguar Land Rover: STJLR.03.5004

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.851
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	42.3
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7.9
Viscosity index, ASTM D2270	162
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7.6
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5500
Sulfated Ash, ASTM D874, Mass %	0.8
Flash Point COC, ASTM D92, °C	220