

Veedol Powertron C2 5W30

Material no. 03201P009

DESCRIPTION

Veedol Powertron C2 5W-30 is a fuel economy universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- Lower fuel consumption
- Suitable for modern catalysts
- Fast cold start
- Safe lubrication film at high temperatures
- Extended oil drain intervals
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Powertron C2 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

PERFORMANCE SPECIFICATIONS

ACEA C2
API SN/CF

Veedol recommends for

Fiat 9.55535-S1
PSA B71 2290
Renault RN 0700

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.856
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	57.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	10.1
Viscosity index, ASTM D2270	167
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7,5
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5500
Sulfated Ash, ASTM D874, Mass %	0,79
Flash Point COC, ASTM D92, °C	232