

Veedol Powertron Ultra 5W40

Material no. 03201P010

DESCRIPTION

Veedol Powertron Ultra 5W-40 motor oil is developed according to the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following benefits are obtained:

- High resistance to shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Reduced formation of combustion ashes
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Powertron Ultra 5W-40 motor oil is specially recommended for passenger car unit injector diesel engines. Further this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEMs and thus has a wide application. It provides reliable protection of after-treatment devices and diesel particulate filters. It is a mid SAPS oil corresponding to Euro 4 and Euro 5 norms.

PERFORMANCE SPECIFICATIONS

ACEA C3
API SN/CF
Ford WSS-M2C917-A

Approval
VW 505 00/505 01

Veedol recommends for
BMW Longlife-04
Fiat 9.55535-GH2/S2
GM dexos2™
MB 226.5/229.51,
Porsche A40
Renault RN 0700/RN 0710

TYPICAL CHARACTERISTICS

| | |
|---|-------|
| Density at 15°C, ASTM D4052, g/ml | 0.851 |
| Kinematic viscosity at 40°C, ASTM D445, mm ² /s | 84,7 |
| Kinematic viscosity at 100°C, ASTM D445, mm ² /s | 13,9 |
| Viscosity index, ASTM D2270 | 170 |
| B.N. (HClO ₄ method), ASTM D2896, mg KOH/g | 7,5 |
| Pour point, ASTM D6892, °C | -39 |
| CCS viscosity at -30°C, ASTM D5293, mPa.s | 5970 |
| Sulfated Ash, ASTM D874, Mass % | 0,8 |
| Flash Point COC, ASTM D92, °C | 235 |

Version 2020-01

Veedol Deutschland GmbH
Hans-Böckler-Straße 10
40764 Langenfeld, Germany
Tel.: +49 (0) 2173 893 30-30
Fax: +49 (0) 2173 893 30-39
Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.