

# Veedol Powertron Plus 5W40

Material-Nr. 03201P012

## DESCRIPTION

A very modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

## APPLICATION

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

## PERFORMANCE SPECIFICATIONS

ACEA A3/B4  
API SN/CF

**Approvals**  
VW 502 00  
VW 505 00

### Veedol recommends for

BMW Longlife-01  
MB 226.5  
MB 229.3  
Opel GM-LL-B-025  
Porsche A40  
PSA B71 2296  
Renault RN 0700  
Renault RN 0710

## TYPICAL CHARACTERISTICS

|   |       |
|---|-------|
| Density at 15°C, ASTM D4052, g/ml                           | 0.858 |
| Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s  | 86.0  |
| Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s | 14.4  |
| Viscosity index, ASTM D2270                                 | 175   |
| B.N. (HClO <sub>4</sub> method), ASTM D2896, mg KOH/g       | 10.5  |
| Pour point, ASTM D6892, °C                                  | -45   |
| CCS viscosity at -30°C, ASTM D5293, mPa.s                   | 6100  |
| Sulfated Ash, ASTM D874, Mass %                             | 1.27  |
| Flash Point COC, ASTM D92, °C                               | 220   |