

Veedol Powertron Extra 5W40

Material-Nr. 03201P016

DESCRIPTION

- Fuel saving in partial and full load operation mode
- Very high and stable viscosity index
- Excellent shear stability
- Excellent cold-starting properties
- A reliable lubricant film, even at high temperatures
- Excellent detergent and dispersing properties
- Strong protection against wear, corrosion and foam formation

APPLICATION

High-performance motor oil, suitable for modern gasoline and diesel engines with and without turbocharger in passenger cars and vans.

PERFORMANCE SPECIFICATIONS

ACEA A3/B4
API SN/CF

Approvals

MB Approval 229.5
VW 502 00/505 00

Veedol recommends for

BMW Longlife-01
MB 226.5
MB 229.3
Porsche A40
PSA B71 2296
Renault RN 0700
Renault RN 0710

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.857
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	83.3
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13.8
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-45
CCS viscosity at -30°C, ASTM D5293, mPa.s	6300
Sulfated Ash, ASTM D874, Mass %	1.1
Flash Point COC, ASTM D92, °C	228