

Veedol Powertron J 5W30

Material no. 03201P025

DESCRIPTION

Veedol Powertron J 5W-30 is a fuel economy universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to give the following benefits:

- Lower fuel consumption
- Suitable for modern catalysts
- Fast cold start
- Safe lubrication film at high temperatures
- Extended oil drain intervals
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Powertron J 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in modern Japanese passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particulate filters.

PERFORMANCE SPECIFICATIONS

ACEA C2
API SN/CF

Veedol recommends for

Modern Japanese cars for which a C2 5W30 oil is specified

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.856
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	57.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	10.1
Viscosity index, ASTM D2270	167
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7,5
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5500
Sulfated Ash, ASTM D874, Mass %	0,79
Flash Point COC, ASTM D92, °C	232