

Veedol Powertron FE 5W30

Material no. 03201P030

DESCRIPTION

- fuel saving in partial and full load operation mode
- high and stable viscosity index
- Excellent shear stability
- excellent cold-starting properties
- excellent protection against oxidation
- Reliable lubricant film, even at high temperatures
- Excellent detergent and dispersing properties
- extensive protection against corrosion and foam formation

APPLICATION

Veedol Powertron FE 5W30 is a fuel-saving motor oil especially formulated for modern gasoline engines in passenger cars.

PERFORMANCE SPECIFICATIONS

API SN/RC
API SN Plus
Ford WSS-M2C945-A
Ford WSS-M2C946-A
Ford WSS-M2C947-A
ILSAC: GF-5

Approval

dexos1TM Gen 2 D120BAAJ160

Veedol recommends for

Chrysler MS 6395

TYPICAL CHARACTERISTICS

| | |
|---|-------|
| Density at 15°C, ASTM D4052, g/ml | 0.853 |
| Kinematic viscosity at 40°C, ASTM D445, mm ² /s | 60.9 |
| Kinematic viscosity at 100°C, ASTM D445, mm ² /s | 10.4 |
| Viscosity index, ASTM D2270 | 159 |
| B.N. (HClO ₄ method), ASTM D2896, mg KOH/g | 9.2 |
| Pour point, ASTM D6892, °C | -45 |
| CCS viscosity at -30°C, ASTM D5293, mPa.s | 5800 |
| Sulfated Ash, ASTM D874, Mass % | 0.94 |
| Flash Point COC, ASTM D92, °C | 221 |