

# Veedol Powertron Racing 5W50

Material no. 03201P031

## DESCRIPTION

A fully synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

## APPLICATION

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

## PERFORMANCE SPECIFICATIONS

ACEA A3/B4  
API SN/CF

### Veedol recommends for

BMW Longlife-01  
MB 229.3  
VW 501 01  
VW 505 00

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	118
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	18.0
Viscosity index, ASTM D2270	170
B.N. (HClO <sub>4</sub> method), ASTM D2896, mg KOH/g	9.6
Pour point, ASTM D6892, °C	-30
CCS viscosity at -30°C, ASTM D5293, mPa.s	6200
Sulfated Ash, ASTM D874, Mass %	1.1
Flash Point COC, ASTM D92, °C	235