

# Veedol Sintron Ultra 0W30

Material no. 03201T001

## DESCRIPTION

This sophisticated full-synthetic fuel economy universal motor oil is produced with high quality synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

## APPLICATION

This universal fuel economy synthetic motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

## PERFORMANCE SPECIFICATIONS

ACEA A3/B4  
API SM

### Veedol recommends for

MB 229.3  
VW 502 00  
VW 505 00

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052 g/ml	0.844
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	66.0
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	11.9
Viscosity index, ASTM D2270	179
B.N. (HClO <sub>4</sub> method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-51
Sulfated Ash, ASTM D874, Mass %	1.1
Flash Point COC, ASTM D92, °C	220
CCS viscosity at -35°C, ASTM D5293, mPa.s	5600