

Veedol Sintron Ultra 0W40

Material no. 03201T002

DESCRIPTION

A nowadays universal full-synthetic motor oil produced with high quality synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

This universal synthetic motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. Its low viscosity enables the application of this motor oil under extreme conditions.

PERFORMANCE SPECIFICATIONS

ACEA A3/B4
API SN
Ford WSS-M2C937-A

Approval
MB Approval 229.5

Veedol recommends for
BMW Longlife-01
Porsche A40
Renault RN 0700
Renault RN 0710
VW 502 00
VW 505 00

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.844
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	80.1
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13.8
Viscosity index, ASTM D2270	178
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-57
Sulfated Ash, ASTM D874, Mass %	1.09
Flash Point COC, ASTM D92, °C	220
CCS viscosity at -35°C, ASTM D5293, mPa.s	6040

Version 2019-12

Veedol Deutschland GmbH
Hans-Böckler-Straße 10
40764 Langenfeld, Germany
Tel.: +49 (0) 2173 893 30-30
Fax: +49 (0) 2173 893 30-39
Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.