

Veedol Sintron Longlife III 5W30

Material no. 03201T003

DESCRIPTION

Veedol Sintron Longlife III 5W-30 is a fuel economy, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- Lower fuel consumption
- Mid SAPS content
- Suitable for modern catalysts
- Fast cold start
- Safe lubrication film at high temperatures
- Extended oil drain intervals
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Sintron Longlife III 5W-30 is a specially composed motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the latest VW 504.00/507.00 requirements, in practice also called VW Longlife III oils.

PERFORMANCE SPECIFICATIONS

ACEA C3
API SN

Approvals

MB Approval 229.51
VW 504 00
VW 507 00

Veedol recommends for

BMW Longlife-04
Porsche C30
VW 503 01

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.853
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	70
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.6
Viscosity index, ASTM D2270	161
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	6.3
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5600
Sulfated Ash, ASTM D874, Mass %	0.7
Flash Point COC, ASTM D92, °C	230

Version 2019-12