



Veedol Sintron Longlife III Plus 5W30

Material no. 03201T003

DESCRIPTION

Veedol Sintron LongLife III Plus 5W-30 is a fuel economy, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to give the following benefits:

- Lower fuel consumption
- Mid SAPS content
- Suitable for modern catalysts
- Fast cold start
- Safe lubrication film at high temperatures
- Extended oil drain intervals up to 30000 km or 2 years
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Sintron LongLife III Plus 5W-30 is a specially composed motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particulate filters. Due to its special composition it is approved for the latest VW 504 00/507 00 standard, in practice also called a VW Longlife III oil.

PERFORMANCE SPECIFICATIONS

ACEA C3
API SN

Approvals

MB-Approval 229.51
VW 504 00/507 00

Veedol recommends for

BMW Longlife-04
Porsche C30
VW 503 01

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.853
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	70
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.6
Viscosity index, ASTM D2270	161
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	6.3
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5600
Sulfated Ash, ASTM D874, Mass %	0.7
Flash Point COC, ASTM D92, °C	230

Version 2022-10

Veedol Deutschland GmbH
Hans-Böckler-Straße 10
40764 Langenfeld, Germany
Tel.: +49 (0) 2173 893 30-30
Fax: +49 (0) 2173 893 30-39
Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.