

Veedol Sintron C4 5W30

Material no. 03201T004

DESCRIPTION

A fuel economy, synthetic motor oil, developed according the most recent technology, based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated.

- a lower fuel consumption
- suitable for modern catalyts
- low combustion ash building (low SAPS)
- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

A fuel economy, specially composed synthetic motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles for which the Renault specification RN0720 is asked and are equipped with modern three way catalyts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

Warning: These oils have the lowest SAPS limits and may be unsuitable for use in some engines.

PERFORMANCE SPECIFICATIONS

ACEA C3
ACEA C4

Approval
Renault RN 0720

Veedol recommends for
Fiat 9.55535-S4
MB 226.51
MB 229.51

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	67.1
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.8
Viscosity index, ASTM D2270	173
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	6.4
Pour point, ASTM D6892, °C	-45
CCS viscosity at -30°C, ASTM D5293, mPa.s	5800
Sulfated Ash, ASTM D874, Mass %	0.5
Flash Point COC, ASTM D92, °C	220

Version 2019-12