

Veedol Sintron C1 5W30

Material no. 03201T005

DESCRIPTION

A fuel economy, universal, synthetic motor oil, developed according the most recent technology, based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated:

- a lower fuel consumption
- suitable for modern catalysts
- low combustion ash building (low SAPS)
- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

A universal, synthetic, fuel economy, specially composed motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

Warning: These oils have the lowest SAPS limits and may be unsuitable for use in some engines.

PERFORMANCE SPECIFICATIONS

ACEA C1
ACEA C2
Ford WSS-M2C934-B

Veedol recommends for

Jaguar Land Rover: STJLR.03.5005
Jaso DL-1

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	67.1
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.8
Viscosity index, ASTM D2270	173
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	6.4
Pour point, ASTM D6892, °C	-45
CCS viscosity at -30°C, ASTM D5293, mPa.s	5800
Sulfated Ash, ASTM D874, Mass %	0.5
Flash Point COC, ASTM D92, °C	220

Version 2019-12

Veedol Deutschland GmbH
Hans-Böckler-Straße 10
40764 Langenfeld, Germany
Tel.: +49 (0) 2173 893 30-30
Fax: +49 (0) 2173 893 30-39
Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.