



The Professional's Choice



Veedol Sintron C1 5W30

Material no. 03201T005

DESCRIPTION

This is a full synthetic lubricant based on carefully selected very high quality base oils. This is a "LOW SAPS" oil for gasoline/LPG and diesel engines of passenger cars with or without turbo, requiring the lowest level of sulphated ash, phosphorus and sulfur and providing fuel economy.

- Aftertreatment protection: full aftertreatment system protection.
- Total engine protection: outstanding engine cleanliness and durability.
- Fuel economy: lower fuel consumption and CO₂ emissions.

APPLICATION

This oil is specifically designed for the newest generation (Euro 4) gasoline and diesel engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil. It procures a significant improvement in fuel economy. This engine oil can also be used, where ILSAC GF-4 oils are recommended.

PERFORMANCE SPECIFICATIONS

ACEA C1
ACEA C2
Ford WSS-M2C934-B

Veedol recommends for:

Jaguar Land Rover: STJLR.03.5005
Jaso DL-1

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	67.1
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	11.8
Viscosity index, ASTM D2270	173
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	6.4
Pour point, ASTM D6892, °C	-45
CCS viscosity at -30°C, ASTM D5293, mPa.s	5800
Sulfated Ash, ASTM D874, Mass %	0.5
Flash Point COC, ASTM D92, °C	220

Version 2019-11

Veedol Deutschland GmbH
Hans-Böckler-Straße 10
40764 Langenfeld, Germany
Tel.: +49 (0) 2173 893 30-30
Fax: +49 (0) 2173 893 30-39
Mail: info@veedol.com

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.