

Veedol Sintron F 5W30

Material no. 03201T007

DESCRIPTION

This modern synthetic fuel economy motor oil is produced with special selected synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

APPLICATION

This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This motor oil is specially developed for those cars, that ask for motor oils that fulfill the recent requirements of the OEM's. This oil is fully backward compatible with Ford M2C 913-A, B and C.

PERFORMANCE SPECIFICATIONS

ACEA A1/B1
ACEA A5/B5
API SL/CF
Ford WSS-M2C913-C/D

Veedol recommends for

Jaguar Land Rover: STJLR.03.5003
Renault RN 0700

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	55.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.95
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	4200
Sulfated Ash, ASTM D874, Mass %	1.09
Flash Point COC, ASTM D92, °C	210