

Veedol Sintron V 0W20

Material no. 03201T019

DESCRIPTION

- High fuel economy
- High and stable viscosity index
- Good resistance against shearing
- Very fast cold start, even at very low temperatures
- Safe lubrication film at very high temperatures
- Very good detergency and dispersion power
- Very strong protection against wear, corrosion and foaming

APPLICATION

A fuel economy, specially formulated engine oil suitable for petrol and diesel engines of Volvo cars where the manufacturer prescribes a product that meets the specification VCC RBS0-2AE with viscosity SAE 0W20.

PERFORMANCE SPECIFICATIONS

ACEA A1/B1
ACEA C5
API SN

Veedol recommends for
Volvo VCC RBS0-2AE

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.845
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	47.9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.0
Viscosity index, ASTM D2270	172
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C -	48
Sulfated Ash, ASTM D874, Mass %	0.8
Flash Point COC, ASTM D92, °C	224