

Veedol Sintron V 0W30

Material no. 03201T022

DESCRIPTION

This modern synthetic fuel economy motor oil is produced with special selected synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

APPLICATION

This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

PERFORMANCE SPECIFICATIONS

ACEA A5/B5
API SL/CF

Veedol recommends for:
Volvo VCC 95200377

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.844
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	53.2
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	10.0
Viscosity index, ASTM D2270	180
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.0
Pour point, ASTM D6892, °C	-45
Sulfated Ash, ASTM D874, Mass %	1.09
Flash Point COC, ASTM D92, °C	220
CCS viscosity at -35°C, ASTM D5293, mPa.s	6000