

Veedol Sintron P 0W30

Material-Nr. 03201T023

DESCRIPTION

A synthetic, fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalyts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

This universal, synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalyts and diesel particle filters.

PERFORMANCE SPECIFICATIONS

ACEA C2

Veedol recommends for:

Fiat 9.55535-DS1/-GS1
PSA B71 2312

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.842
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	52.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.6
Viscosity index, ASTM D2270	172
Pour point, ASTM D6892, °C	-48
Sulfated Ash, ASTM D874, Mass %	0.56
Flash Point COC, ASTM D92, °C	230
CCS viscosity at -35°C, ASTM D5293, mPa.s	5850