

Veedol Sintron F 0W30

Material no. 03201T025

DESCRIPTION

A synthetic, fuel economy motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

This synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Very suitable for Ford engines where the manufacturer prescribes a product that meets the specification Ford WSS-M2C950-A with the viscosity SAE 0W30.

PERFORMANCE SPECIFICATIONS

ACEA C2
Ford WSS-M2C950-A

Veedol recommends for
Jaguar Land Rover: STJLR.03.5007

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.847
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	45.6
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	9.4
Viscosity index, ASTM D2270	196
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C	-48
Sulfated Ash, ASTM D874, Mass %	0.79
Flash Point COC, ASTM D92, °C	210
CCS viscosity at -35°C, ASTM D5293, mPa.s	5600