

Veedol Sintron Ultra 0W20

Material no. 03201T026

DESCRIPTION

A fuel economy motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a good resistance against shearing
- a fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

APPLICATION

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. By its unique composition, this oil is also excellent for Hybrid and other Eco versions as brought by various OEM's in the market. Due to its special composition, this product may well be applied to very low temperatures, such as under arctic conditions may occur.

PERFORMANCE SPECIFICATIONS

API SN/RC/SN Plus
Ilsac: GF-5
Ford WSS-M2C945-A
Ford WSS-M2C946-A
Ford WSS-M2C947-A

Approval

GM dexos1TM Gen 2 D120AAAJ160

Veedol recommends for

Chrysler MS 6395
Fiat 9.55535-CR1
Fiat 9.55535-GSX

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.849
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	45.6
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	8.69
Viscosity index, ASTM D2270	173
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	8.1
Pour point, ASTM D6892, °C	-48
Sulfated Ash, ASTM D874, Mass %	0.88
Flash Point COC, ASTM D92, °C	222
CCS viscosity at -35°C, ASTM D5293, mPa.s	5710

Version 2019-12