

# Veedol Sintron C3 0W30

Material no. 03201T033

## DESCRIPTION

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is a "low saps", low viscosity engine oil of the latest generation, for the lubrication of gasoline and diesel engines. Significant fuel economy can be obtained, compared to standard motor oils.

- Total engine protection: performance in keeping the engine clean.
- Fuel economy: superior fuel economy and CO2 reduction.
- Cold start: excellent fluidity at low temperature.

## APPLICATION

This product is aimed and specially formulated for usage in diesel and gasoline engines of BMW group passenger vehicles. It can also be used in other OEM diesel and gasoline engines where there is a need for a 0W30 grade low SAPS oil.

## PERFORMANCE SPECIFICATIONS

ACEA C3  
API SN/CF

### Veedol recommends for

BMW Longlife-04  
Fiat 9.55535-DS1  
Fiat 9.55535-GS1  
MB 229.31

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	66.6
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	12.1
Viscosity index, ASTM D2270	182
B.N. (HClO4 method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C	-54
Sulfated Ash, ASTM D874, Mass %	0.8
Flash Point COC, ASTM D92, °C	224
CCS viscosity at -35°C, ASTM D5293, mPa.s	5900