

Veedol Diesel Star Ultra 10W40

Material no. 03202M108

DESCRIPTION

Veedol Diesel Star Ultra 10W-40 is formulated with synthetic base oils and a well balanced choice of additives. This engine oil gives the following benefits:

- Very powerful detergency minimizing deposits in the hot zone of the engine
- Very strong dispersion that restricts deposits and cold sludge to a minimum
- Powerful protection against corrosion and foaming
- High and stable viscosity index
- Powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners
- Extended oil drain intervals

APPLICATION

This engine lubricant is applicable to diesel engines (normal or turboaspirated) even under the toughest operating conditions and all year round use. This engine oil has a special additive system and may therefore be used when fuels with relatively high sulphur content are involved. This product is also suitable for application in Euro 2 and Euro 3 engines. It is not suitable for Euro 4 engines with particulate filters.

PERFORMANCE SPECIFICATIONS

ACEA A3/B4, E7	Veedol recommends for	Global DHD-1
API CI-4/SL	Allison C4	Jaso DH-1
	Caterpillar ECF-2	Mack EO-M PLUS/EO-N
	Cummins CES 20076	MAN M3275-1
	Cummins CES 20077	MB 228.3/229.1
	Cummins CES 20078	MTU Oil Category 2
	Detroit Diesel 93K215	Renault RLD-2/RLD
	Deutz DQC-III-10	Volvo VDS-3

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.866
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	88.4
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13.8
Viscosity index, ASTM D2270	160
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	11.9
Pour point, ASTM D6892, °C	-39
CCS viscosity at -25°C, ASTM D5293, mPa.s	5500
Sulfated Ash, ASTM D874, Mass %	1.49
Flash Point COC, ASTM D92, °C	227