

# Veedol Hypoid Gear Oil 85W-140

Material no. 03203M215

## DESCRIPTION

**Veedol Hypoid Gear Oil 85W-140** is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP additives to give the following benefits:

- Long transmission life
- Excellent resistance to oxidation
- Very high activity against wear, corrosion and foaming
- Very good EP properties

## APPLICATION

This gear oil is used in hypoid differentials under very heavy duty conditions and may be used in all transmissions that require heavy duty EP transmission oils.

## PERFORMANCE SPECIFICATIONS

API GL-5  
MIL-L-2105 C/D

**Veedol recommends for**  
ZF TE-ML 05A/07A/12E/16B/16C/16D/17B/19B

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.908
Kinematic viscosity at 40°C ASTM D445, mm <sup>2</sup> /s	367
Kinematic viscosity at 100°C ASTM D445, mm <sup>2</sup> /s	26.1
Viscosity index ASTM D2270	95
Pour point, ASTM D6892, °C	-15
Copper corrosion, ASTM D130	1B
Flash Point COC, ASTM D92, °C	215