



Veedol Gear Oil LD 75W-80

Material no. 03203P203

DESCRIPTION

Veedol Gear Oil LD 75W-80 is a synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP additives to obtain the following properties:

- Excellent thermal stability
- Very high activity against wear, corrosion and foam
- Low pour point
- Very high quality EP-properties
- Good clutch-switch performance at low temperatures
- Long durability
- Fuel economy

APPLICATION

This gear oil is specially developed for gearboxes under very heavy duty conditions, together with high temperatures. This oil can also be used for extended drain intervals.

PERFORMANCE SPECIFICATIONS

API GL-4

Veedol recommends for

DAF
Eaton Extended drain
Iveco
MAN 341 E-3/Z-4
MB 235.4
Renault B0032/2 Annex 3
Volvo 97307/97305
ZF TE-ML 01L/02L/08/13/16K/24A

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.860
Kinematic viscosity at 40°C ASTM D445, mm ² /s	57.9
Kinematic viscosity at 100°C ASTM D445, mm ² /s	9.75
Viscosity index ASTM D2270	154
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	80000
Flash Point COC, ASTM D92, °C	234