



# Veedol Gear Oil RPC 75W80

Material no. 03203P204

## DESCRIPTION

This transmission oil is a universal, mineral multigrade lubricating oil for mechanical transmissions, with EP-properties. Due to the addition of high quality solvent refined base oils and special additives this gear oil has the following properties:

- a very high activity against wear, corrosion and foam
- an excellent resistance against oxidation
- low viscosity at low temperatures
- very good EP-properties
- a high and stable viscosity index

## APPLICATION

This special transmission oil is used in gearboxes where a good clutch-switch performance is necessary. This gear oil can also be used where the manufacturer of the gearbox prescribes a gear oil with a low viscosity.

## PERFORMANCE SPECIFICATIONS

API GL-4 +  
Ford WSD-M2C200-D  
Ford ESD-M2C186-A

**Veedol recommends for**  
Fiat 9.55550-MX3/-MZ1  
GM 1940182/1940768  
Honda MTF 94  
MB 235.10  
Nissan MT-XZ  
PSA B71 2330/9730 A8  
Volvo 97308/97309/97310

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.871
Kinematic viscosity at 40°C ASTM D445, mm <sup>2</sup> /s	45.8
Kinematic viscosity at 100°C ASTM D445, mm <sup>2</sup> /s	9.1
Viscosity index ASTM D2270	185
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	142.000
Flash Point COC, ASTM D92, °C	205