

Veedol Transmission Synthetic LD 75W-90

Material no. 03203T209

DESCRIPTION

Veedol Transmission Synthetic LD 75W-90 is an universal full-synthetic gear oil based on high quality synthetic base oils and special EP additives to give the following benefits:

- Advanced protection under high-speed/shock-load or low-speed/high-torque conditions.
- Very strong activity against wear, corrosion and foaming
- Low pour point
- Very capable extreme pressure properties
- Widely usable

APPLICATION

This universal gear oil is developed for manual transmissions and hypoid differentials in heavy trucks. This so called "Total Drive Line" oil is widely usable as a universal product.

PERFORMANCE SPECIFICATIONS

API GL-5/GL-4/MT-1
SAE J 2360

Veedol recommends for
DAF
Iveco
MAN 342 S1/341 Z2
MB 235.8

Scania STO 2/STO 1
Volvo 97312
ZF TE-ML 02B/05A/12L/
12N/16F/17B/19C/21A

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.868
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	105
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	15.5
Viscosity index, ASTM D2270	158
Pour point, ASTM D6892, °C	-61
CCS viscosity at -40°C, ASTM D5293, mPa.s	65000
Flash Point COC, ASTM D92, °C	202