

Veedol Transmission LS 75W-140

Material no. 03203T218

DESCRIPTION

Veedol Transmission LS 75W-140 is a semi synthetic lubricant based on carefully selected highly refined base oils. This is a high performance transmission oil for all differentials, including those equipped with a "limited slip" mechanism. It is characterized by an exceptionally high viscosity stability at different temperatures and a very high fluidity at low temperature. This transmission oil gives the following benefits:

- Excellent frictional properties: very smooth gear shifting, with no vibration
- Anti-wear protection: extended transmission life
- Extended oil life: excellent thermal and oxidation stability

APPLICATION

This product is used in highly loaded axles and reduction gears of cars, trucks and off-road equipment. It has "limited-slip" characteristics and is specifically recommended for 4X4 vehicles.

PERFORMANCE SPECIFICATIONS

API GL-5
MIL-L-2105 C/D

Veedol recommends for
BMW MSP/A
FORD WSS-M2C192-A/
192A+/118-A/187-A
GM 1942386/12346140

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	905
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	170
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	26.5
Viscosity index, ASTM D2270	195
Pour point, ASTM D6892, °C	-51
Flash Point COC, ASTM D92, °C	190