

Veedol ATF II-D

Material no. 03204M254

DESCRIPTION

Veedol ATF II-D is a very high grade automatic transmission fluid formulated with solvent refined base oils and a number of select additives to obtain the following properties:

- High and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- Positive activity against wear, corrosion and foaming
- Specific friction properties
- Perfect compatibility with seals and non-ferro metals
- Red coloured

APPLICATION

This fluid is used for automatic gearboxes, power steering units, torque converters and other equipment for which an ATF Dexron II-D fluid is required.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Allison C4
Caterpillar TO-2
Ford M2C-138CJ
Mercon
GM 6137-M Dexron II-D
MAN 339 V1/Z1
MB 236.5
MB 236.7
Voith H55.6335xx
ZF TE-ML 03D
ZF TE-ML 04D
ZF TE-ML 09
ZF TE-ML 11A
ZF TE-ML 14A
ZF TE-ML 17C

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.856
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	37
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7.4
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	3
Pour point, ASTM D6892, °C	-39
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	45000
Colour, VISUAL	RED

Version 2019-12