



Veedol ATF III-G

Material no. 03204P253

DESCRIPTION

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

APPLICATION

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Allison C4
 Ford Mercon
 GM 6417-M Dexron III-G
 MAN 339 V1/Z1
 MB 236.5
 MB 236.9
 Voith H55.6335xx
 Volvo STD 1273,40 (97340)
 Volvo STD 1273,41 (97341)
 ZF TE-ML 03D
 ZF TE-ML 04D
 ZF TE-ML 09
 ZF TE-ML 11B
 ZF TE-ML 14A
 ZF TE-ML 17C

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.855
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	33,9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7,1
Viscosity index, ASTM D2270	179
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	17500
Flash Point COC, ASTM D92, °C	196
Colour, VISUAL	RED