

Veedol ATF VI

Material no. 03204P257

DESCRIPTION

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- longer life time of the liquid
- exceeds the properties of Dexron III and II liquids
- red coloured

APPLICATION

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

GM Dexron VI
MB 236.41
Voith H55.6335xx

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.847
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	30
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	6.0
Viscosity index, ASTM D2270	151
Pour point, ASTM D6892, °C	- 45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	12000
Colour, VISUAL	RED