

Veedol ATF III-AP

Material no. 03204T251

DESCRIPTION

Veedol ATF III-AP is a full synthetic automatic transmission fluid, based on synthetic base oils and formulated with special friction modifiers to give the following benefits:

- Excellent stability against oxidation
- Specific friction properties and consequently low noise and smooth switching
- Compatible with synthetic seals
- Quick oil flow at cold start conditions
- Very strong protection against wear, corrosion and foaming

APPLICATION

This fluid may be used for the automatic transmissions, of a wide range of cars, including Japanese cars, with the specifications mentioned.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Aisin-Warner JWS 3309/JWS 3314/JWS 3317
 Allison TES 295
 BMW ETL 7045E/ETL 8072B/LA 2634/LT 71141
 Chrysler ATF +3/+4
 Fiat 9.55550-AV4
 Ford Mercon V/WSS-M2C922-A1
 GM Dexron III-H
 Honda ATF Z-1
 Hyundai SP-III
 MB 236.3/236.7/236.10/236.11
 Nissan Matic-K/W
 PSA P/N Z 000169756
 Toyota Type T-IV
 VW G 052 055/G 052 162/G 052 533/G 052 990/G 055 025

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.849
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	32.7
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7.02
Viscosity index, ASTM D2270	184
Pour point, ASTM D6892, °C	-48
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	12000
Flash Point COC, ASTM D92, °C	218
Colour, VISUAL	RED