

Veedol ATF 8-G

Material no. 03204T259

DESCRIPTION

- Very good oxidation stability and very high thermal stability
- Excellent and very stable friction characteristics for longer oil change intervals
- Outstanding fuel saving potential
- Excellent lubrication
- Extensive protection against foaming
- Very good protection against wear
- Very high and stable viscosity index

APPLICATION

ATF 8-G was formulated especially for ZF 8HP transmissions. Thanks to its very low viscosity, this product makes a major contribution to reducing consumption. ATF 8 G can be used among other things for the ZF transmissions of the HP-8 series (8HP45, 8HP55, 8HP70 and 8HP90) and also in certain ZF 6HP transmissions of some VAG models.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

BMW 83222152426
Chrysler 68157995AA
Fiat 9.55550-AV5
Jaguar 02JDE26444
Land Rover LR023288
VW G 060 162

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.845
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	28.1
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	5.94
Viscosity index, ASTM D2270	164
Pour point, ASTM D6892, °C	-48
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	9500
Flash Point COC, ASTM D92, °C	210
Colour, VISUAL	GREEN