

Veedol Racing Plus 2T

Material no. 03206P351

DESCRIPTION

- Perfect lubrication of all motor parts
- Active detergency, preventing deposits in the combustion zone and in the scavenger ports
- Prevents spark plugs from fouling, thereby securing an optimal output of the engine
- Very effective protection against wear and corrosion
- Very limited formation of smoke
- Self-mixing

APPLICATION

This two stroke engine oil is recommended for the lubrication of high speed air-cooled two stroke engines under heavy duty loads. It may also be used for water cooled two stroke engines (with radiator type cooling systems).

PERFORMANCE SPECIFICATIONS

API TC

Veedol recommends for

ISO L-EGD

Jaso FC/FD

TYPICAL CHARACTERISTICS

| | |
|---|----------------|
| Density at 15°C, ASTM D4052, g/ml | 0.880 |
| Kinematic viscosity at 40°C, ASTM D445, mm ² /s | 56.3 |
| Kinematic viscosity at 100°C, ASTM D445, mm ² /s | 8.2 |
| Viscosity index, ASTM D2270 | 115 |
| B.N. (HClO ₄ method), ASTM D2896, mg KOH/g | 1.7 |
| Flash Point COC, ASTM D92, °C | 106 |
| Colour, VISUAL | BLACKISH GREEN |