



Veedol ATF II-D

Material no. 03204M254

DESCRIPTION

Veedol ATF II-D is a quality automatic transmission fluid formulated with solvent refined base oils and a number of select additives to give the following benefits:

- Positive activity against wear, corrosion and foaming
- High and stable viscosity index
- Very good resistance to oxidation
- Specific friction properties
- Perfect compatibility with seals and non-ferro metals

APPLICATION

This red coloured fluid is used for automatic gearboxes, power steering units, torque converters and other equipment for which an ATF Dexron II-D fluid is required. It is suitable for older vehicles.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Allison C4
 Caterpillar TO-2
 Daimler Truck DTFR 13C140
 Ford M2C-138CJ
 Mercon
 GM 6137-M Dexron II-D
 MAN 339 V1/Z1
 MB 236.5/236.7
 Voith H55.6335xx
 ZF TE-ML 03D/04D/ 09/11A/14A/17C

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.856
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	37
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7.4
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	3
Pour point, ASTM D6892, °C	-39
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	45000
Colour, VISUAL	RED