

Veedol ATF CVT

Material no. 03204P256

DESCRIPTION

Veedol ATF CVT is a red coloured full synthetic fluid suitable for use in most CVT gearboxes. It gives the following benefits:

- Excellent wear protection
- Neutral towards synthetic sealing materials, thereby preventing leaks
- Vibration-free operation
- Long service intervals/long transmission life

APPLICATION

This fluid was developed especially for use in modern, continuous variable transmissions (CVT) and guarantees smooth and easy shifting, in combination with significant fuel economy.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Audi TL 52180	Mazda CVTF 3320
BMW 83 22 2 344 207/ATF 5/EZL799/EZL799A	MB 236.20/CVT28
Daihatsu AMIX CVTF DFE/AMIX CVTF-DC	Mini EZL799/EZL799A/CVT V1
Dodge NS-2/CVTf+4	Mitsubishi CVTF J-1
Ford Mercon C/WSS-M2C928-A/ WSS-M2C933-A	Nissan NS-1/NS-2/NS-3/Matic W
Fujijyuuko i-CVTf FG	Punch EZL799/EZL799A
GM CVTF GREEN 2/SATURN DEX-CVT	Renault ELFMATIC
Honda HCF-2/HMMF (No Start Clutch)	Subaru e-CVTf
Hyundai SP-CVT1	Suzuki CVTF 3320
Jeep NS-2/CVTf+4	Toyota TC/CVT FE
Kia SP-CVT 1	Volvo CVT 4959
	VW G 052 180/G 052 516

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.844
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	32.9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	7.1
Viscosity index, ASTM D2270	187
Pour point, ASTM D6892, °C	-54
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	10600
Flash Point COC, ASTM D92, °C	188
Colour, VISUAL	RED